

Specifications

| | |
|----------------|---|
| CPU | Intel® Core™ i7 3630QM, 2.4GHz (6M Cache, up to 3.40 GHz) |
| | Intel® Core™ i5 3320M, 2.6GHz (3M Cache, up to 3.30 GHz) |
| | Intel® Core™ i3 3120M, 2.5GHz (3M Cache, 2.50 GHz) |
| | Intel® Bay Trail-D Platform, Celeron® Processor J1900 (2.0 GHz, 2M Cache) |
| System Memory | 2 x DDR3 SO-DIMM 1333MHz, up to 16GB |
| OS Support | POS Ready 2009, POS Ready 7, XP Pro, Vista, Linux, Windows 7 |
| HDD Storage | 1 x 2.5" SATA Bay for HDD or SSD |
| Compact Flash | CFast Slot for SATAI / SATA II |
| Display | 1024 x 768 Pixel |
| Touch | 5 Wire Resistive / capacitive touch screen |
| Size | 15" |
| Brightness | 300 nits |
| Tilt Angle | 15~80 Degrees (up to 90 degree possible) |
| Power Input | 12VDC 90W, 4-pin Connector with Lock (External Adaptor: 100~240 VAC, 50/60HZ) |
| Weight | 6.7 Kg |
| Dimension (mm) | 391.2(W) x 352.3(H) x 245.0(D) |
| Compliance | FCC / CE / WEEE / RoHS |
| Interface | 4 x COM (3 x DB9 , 1x RJ45 with power output, 5/12V selectable) |
| | 2 x USB3.0 (External), 4 x USB2.0 (External), |
| | 3 x USB 2.0 (Internal, reserved for touch screen, Wi-Fi, and MSR) |
| | 1 x mixed PS2 |
| | 1 x RJ-45, Giga LAN Support |
| | 1 x DB-15, Female |
| | 12VDC Jack for Customer Display or 2nd LCD Display (10.4") |
| | 1 x RJ-11, 12/24 VDC |
| | 1 x Line Out, 1 x MIC In, 1 x Internal Speaker 2W |

Pegasus RPOS-5000

