# WorkForce Pro WF-C869RDTWFC



# Save on energy and cut waste with this reliable 4-in-1 business MFP, featuring predictable printing costs and low user intervention.

Print 84,000 pages<sup>1</sup> without any supply changes with this exemplary business printer, using Epson's super-high-yield Replaceable Ink Pack System (RIPS). Cut intervention downtime and lessen your impact on the environment with a reduction of up to 95 percent on energy<sup>1</sup> and 99 percent on waste<sup>1</sup>. It also uses PrecisionCore technology, renowned for its speed, quality, reliability and efficiency.

## Print 84,000 pages uninterrupted

Thanks to super-high-yield ink supply units, you can print up to 84,000 pages without replacing the ink<sup>1</sup>, that's up to 4.5 times more prints than colour lasers and copiers<sup>2</sup>. It cuts intervention time by up to 98 percent<sup>2</sup> as replacement inks are few and far between.

## The best choice

It uses Epson's most advanced printhead designed for business, PrecisionCore. But that's not all; compared to competitive colour lasers it uses up to 95 percent less power<sup>2</sup> thanks to its no-heat technology. There really is no contest; it also beats lasers and copiers with an up to 99 percent reduction in waste and it's up to 23% quieter than lasers and laser copiers<sup>2</sup>.

## Be more productive

Its first page out time is up to three and a half times faster than competitive products<sup>2</sup>. Wait times and the distance to collect print jobs are minimised too as it's a workgroup printer.

#### DATASHEET / BROCHURE



# **KEY FEATURES**

- Reduce downtime Print up to 84,000 pages without replacing the ink<sup>1</sup>
- Ecological Uses up to 95 percent less power than competitive colour lasers<sup>2</sup>
- Save time Automatic double-sided printing, scanning, copying and faxing
- Built for business Added functionality with software tools such as Epson Open Platform
- PrecisionCore technology Epson's most advanced printhead technology




Scanner type

TECHNOLOGY			
Printing Method	PrecisionCore <sup>™</sup> Print Head		
Nozzle Configuration	800 Nozzles Black, 800 Nozzles per Color		
Minimum Droplet Size 4.6 pl, With Variable-Sized Droplet Technology			
Ink Technology	Replaceable Ink Pack System (RIPS)		
Category Office Workgroup			
All-in-One Functions	Print, Scan, Copy, Fax		
PRINT			
First Page Out	Monochrome 6 Seconds, Colour 6 Seconds		
Printing Speed ISO/IEC 2473	4 24 pages/min Monochrome, 24 pages/min Colour		
Duplex Printing Speed ISO/IEC 24734	16 A4 Pages/min Monochrome, 16 A4 Pages/min Colour		
Printing Speed ISO/IEC 24734 (A3)	4 13 pages/min Monochrome, 13 pages/min Colour		
Duplex Printing Speed ISO/IEC 24734 (A3)	11 A4 Pages/min Monochrome, 11 A4 Pages/min Colour		
Maximum Printing Speed	35 pages/min Colour (plain paper 75 g/m <sup>2</sup> ), 35 pages/min Monochrome (plain paper 75 g/m <sup>2</sup> )		
Printing Resolution	4,800 x 1,200 DPI		
Printing Volume	75,000 pages per month		
	The maximum number of printed pages per month based on the performance capabilities of		
	the printer, including ISO rated print speeds and paper handling capabilities.		
Recommended Duty Cycle	2,000 - 10,000 pages per month		
For detailed information on p	rinting speeds please visit http://www.epson.eu/testing.		
SCAN			
Single-sided scan speed (A4 black)	200 dpi (with ADF); , 25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan		
Doubled-sided scan speed (A4 black)	200 dpi (with ADF); , 45 ipm with ADF scan		
Single-sided scan speed (A4 colour)	200 dpi (with ADF); , 25 ipm with ADF scan 200 dpi (flatbed) 4 sec. with flatbed scan		
Doubled-sided scan speed (A4 colour)	200 dpi (with ADF); , 45 ipm with ADF scan		
Optical Resolution	1,200 DPI x 2,400 DPI (Horizontal x Vertical)		
Optical Resolution (ADF)	600 DPI x 600 DPI (Horizontal x Vertical)		
Advanced document	Scan to Email, Scan to FTP, Scan to Network folders, Computer (Epson Document Capture		
integration Output formats	Pro), Microsoft SharePoint with Epson Document Capture Pro, USB Memory Device / Card JPEG, TIFF, PDF		

WorkForce Pro WF-C869RDTWFC

# WHAT'S IN THE BOX

- Quick Setup Guide
- Main unit
- Warranty Documents
- User manual (CD)
- Power cable
- Paper tray
- Initialization Ink Supply Units



Contact image sensor (CIS)

EPSC **EXCEED YOUR VISION** 

FAX			
Type of fax	Walk-up black and white and colour fax capability		
Fax Transmission Speed	Up to 33.6kbps / Approx. 3 sec/page		
Error correction mode	CCITU/ITU Group3 fax with Error Correction Mode		
Fax speed dials (max)	2,000 names and numbers		
Page memory	Up to 550 pages/ 6MB (ITU-T No. 1 chart)		
Fax Functions	PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Speed Dial, Fax to Folder, Address		
	Book		
COPY			
Copy Speed	Up to 22 ipm Black, Up to 21 ipm Colour		
	*Simplex ADF 600 x 600 dpi (ISO/ IEC 24735)		
Copy resolution (dpi)	600 x 1200		
Reduction / Enlargement	25 % - 400 % Auto fit function		
Maximum number of copies	999		
Maximum Copy Size	A3		
CONNECTIVITY			
Network Printing Protocols	LPR, FTP, IPP, Port 9100, WSD, Net BIOS over TCP/IP, IPPS, PTP over IP, DPS over IP, IS,		
	Bonjour/Airprint		
Network Management	HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, WSD, LLTD, SMTP, LLMNR, POP3, IEEE		
Protocols	802.1X, ARP, GARP, EAP, ICMP, IGMP, DCHP, DNS-SD, HTTPS, XMPP, SMTPS, LDAP,		
	LDAPS, SNMP 1.0, SNMP 2.0c, SNMP 3.0, SNMP Trap		
Network Scanning Protocols			
Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet Interface (1000 Base-T/ 100-		
	Base TX/ 10-Base-T), USB host, Wi-Fi Direct, USB 2.0 Type A (2x), Wireless LAN IEEE		
	802.11a/b/g/n, USB 3.0 Type B		
WLAN Security	WEP 64 Bit, WEP 128 Bit, WPA PSK (TKIP), WPA2 PSK (AES), WPA2 Enterprise (AES)		
Network Protocol	TCP, UDP, HTTP, HTTPS, IPv4, IPv6, IPSEC, SSL/TLS		
PAPER / MEDIA HANDLING			
Paper Formats	A4, A5, A6, B5, C4 (Envelope), C6 (Envelope), No. 10 (Envelope), Letter, 10 x 15 cm, 13 x 18		
	cm, 20 x 25 cm, Legal, A3, B4, B6, C5 (Envelope), DL (Envelope), HLT, EXE, A3+		
Automatic Document Feed	50 pages		
Compatible Paper Weight	64 g/m² - 300 g/m²		
Duplex	Yes		
Standard Paper input	835 Sheets Standard, 85 Sheets MP tray, 750 Sheets paper tray		
Output Tray Capacity	250 Sheets		
Paper Tray Capacity	835 Sheets Standard, 835 Sheets Maximum		
Standard paper tray(s)	85-Sheet Multi-Purpose Tray, 250-sheet paper tray, 500-Sheet paper tray, Cabinet		
Maximum paper input	835		
Rear paper path (special	Yes		
media)			
Number of paper trays	3		



#### WorkForce Pro WF-C869RDTWFC

PAPER FEED RASF		
Paper Input Name	RASF	
Paper Formats	A3+, A3, A4, A5, A6, B4, B5, B6, C4 (Envelope), C5 (Envelope), C6 (Envelope), DL (Envelope),	
	Letter, 10 x 15 cm, 13 x 18 cm, 16:9, HLT, User defined, Legal, Executive, SRA3	
Custom sizes	Min 55x 330 mm to Max 127x 1,200 mm	
Compatible paper weight	64 g/m² - 300 g/m²	
Paper Capacity 1	85 80gsm	
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead, Glossy Photo Paper	
PAPER FEED C1		
Paper Input Name	C1	
Paper Formats	A3, A4, A5, A6, B4, B5, B6, Letter, HLT, Legal, Executive	
Compatible paper weight	64 g/m² - 200 g/m²	
Paper Capacity 1	250 80gsm	
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED C2		
Paper Input Name	C2	
Paper Formats	A3, A4, A5, A6, B4, B5, B6, Letter, Legal, Executive	
Compatible paper weight	64 g/m² - 200 g/m²	
Paper Capacity 1	500 80gsm	
Media type	Plain Paper, Recycled Paper, Colour Paper, Letterhead	
PAPER FEED DUPLEX		
Paper Input Name	Duplex	
raper input Name		
• •	A3, A4, A5, B4, B5, B6, Letter, Legal, Executive	
Paper Formats	A3, A4, A5, B4, B5, B6, Letter, Legal, Executive 64 g/m² - 150 g/m²	
Paper Formats Compatible paper weight	64 g/m² - 150 g/m²	
Paper Formats Compatible paper weight Paper Capacity 1		
Paper Formats Compatible paper weight Paper Capacity 1 Media type	64 g/m² - 150 g/m² 80gsm	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL	64 g/m² - 150 g/m² 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern),	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 (32/64 bit), Windows Server	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 R2, Windows Vista, Windows	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating Systems	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 R2, Windows Server 2012 (64 bit), Windows XP x64, Windows Server 2003 R2	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating Systems	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 (32/64 bit), Windows Vista, Windows Vista (32/64 bit), Windows Vista x64, Windows XP x64, Windows Server 2003 R2 Operation: 6.4 B (A)	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating Systems Sound Power Noise	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 (32/64 bit), Windows Server 2008 R2, Windows Vista x64, Windows XP x64, Windows Server 2003 R2 Operation: 6.4 B (A) Operation: 48 dB (A)	
Paper Formats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating Systems Sound Power Noise Mobile and Cloud printing	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 (32/64 bit), Windows Server 2012 (64 bit), Windows XP x64, Windows Server 2003 R2 Operation: 6.4 B (A) Operation: 6.4 B (A) Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint,	
Paper input Name Paper Pormats Compatible paper weight Paper Capacity 1 Media type GENERAL Energy Use Supply Voltage Compatible Operating Systems Sound Power Noise Mobile and Cloud printing services Power supply	64 g/m <sup>2</sup> - 150 g/m <sup>2</sup> 80gsm Plain Paper, Recycled Paper, Colour Paper, Letterhead 20 Watt (Ready), 0.5 Watt (Power off), 40 Watt (standalone copying, ISO/IEC 24712 pattern), 1.6 Watt (sleep mode), TEC 0.24 kWh/week AC 220 V - 240 V Citrix XenApp 7.x, Linux, Mac OS 10.10.x, Mac OS 10.11, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Microsoft Windows XP (Home Edition / Prof / Prof X64 / Vista), SAP Windows 10, Windows 7, Windows 7 x64, Windows 8 (32/64 bit), Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2003 (32/64 bit), Windows Server 2008 (32/64 bit), Windows Server 2008 R2, Windows Vista x64, Windows XP x64, Windows Server 2003 R2 Operation: 6.4 B (A) Operation: 48 dB (A)	



#### WorkForce Pro WF-C869RDTWFC


ADDITIONAL FEATURES		
Features	Touchscreen, Direct scan-to-print without PC, Direct print from USB	
Panel	Type: Color, Touchscreen, Diagonal: 12.7 cm	
Media Handling	Automatic duplex (A4/A3, plain paper), Portrait & Landscape printing, Rear specialty media feed, Thick Media Support	
Security Functions	Limit access function with Epson Web Config, Secure confidential printing with PIN code release, LDAP Address Book, IPsec, IEEE802.1x, SSL (Server authentication), Panel Admin Mode	
OTHER FEATURES		
Emulations	PCL6, PCL5c, PCL5e, ESC/P-R, PDF 1.7, PostScript 3	
OTHER		
Warranty	12 months On-site service	
	Optional warranty extension available	



SUPPLIES		
• Business Paper - A4 - 500 Sheets	C13S450075	
<ul> <li>Black XL Ink Supply Unit</li> </ul>	C13T973100	22,500 pages
<ul> <li>Cyan XL Ink Supply Unit</li> </ul>	C13T973200	22,000 pages
<ul> <li>Magenta XL Ink Supply Unit</li> </ul>	C13T973300	22,000 pages
<ul> <li>Yellow XL Ink Supply Unit</li> </ul>	C13T973400	22,000 pages
<ul> <li>Black XXL Ink Supply Unit</li> </ul>	C13T974100	86,000 pages
<ul> <li>Cyan XXL Ink Supply Unit</li> </ul>	C13T974200	84,000 pages
<ul> <li>Magenta XXL Ink Supply Unit</li> </ul>	C13T974300	84,000 pages
<ul> <li>Yellow XXL Ink Supply Unit</li> </ul>	C13T974400	84,000 pages
Maintenance box	C13T671400	
Optional Cassette Maintenance Roller	C13S210049	200,000 pages
Standard Cassette Maintenance Roller	C13S210048	200,000 pages
<ul> <li>Double-Sided Photo Quality Inkjet Paper - A4 - 50 Sheets</li> </ul>	C13S400059	

#### WorkForce Pro WF-C869RDTWFC

# **INK YIELD DATA**



\* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

#### **OPTIONAL ACCESSORIES**

- Card Reader Holder C12C932921
- Retractable output tray C12C934171

#### LOGISTICS INFORMATION

ѕки	C11CF34401BR
EAN code	8715946623177
Layer	1 Units



\* Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09 74 75 04 04

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742

Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway +47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zl/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

465-9621 Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min)

Switzerland 022 592 7923 Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. Approx. page yield. Actual yield will vary depending on images printed and usage conditions. For more information visit www.epson.eu/pageyield. Initialisation inks only have enough ink to support printer start up, new inks have to be purchased or supplied for normal operation. 2. For more information, visit www.epson.eu/inkjetsaving



Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners. Product information is subject to change without prior notice.