

Portable Data Collector



Pegasus

DC - 7010

Portable Data Collector

Sleek and stylish exterior with a tactile 21-key Keypad, ensures comfortable use and easy entry of barcode scan, data key-in, editing and navigation.

Portable Data Collector

Pegasus

DC - 7010

Portable Data Terminal With Cradle Look-up function added, comes with cradle that offers communication and recharge DC-7010 is a battery-operated portable data collector with look-up function. Equipped with a high quality laser engine, the ergonomic-built data terminal offers its users with efficiency and comfort, and is ideal for long-time use. Its 1700mAh Lithium-ion battery guarantees at least 24 hrs of operation time. In addition, DC-7010 provides a user friendly job generator utility. You don't need to applications by writing the program source code, ensuring that the once incomprehensible development process becomes distinct and effortless.

Features

- The Job generator allows users to easily design their own applications.
- High quality laser engine to ensure accurate bar-code reading
- A cradle offers communication and recharge via RS-232 or USB cables
- A sharp LCD with back-light furnishes clear pleasant viewing
- Look-up function provides on-site checking, updating and editing

| System | |
|----------------------|--|
| CPU | 32 bit CPU, with 512K Program flash RAM |
| Memory | 2M Byte SRAM (1MB lookup table) |
| Data Capacity | 1 MB or 35,000 records |
| Display | 128x128 graphic dots FSTN LCD with blue back light |
| Keypad | 21 rubber key ikeys, function keys, scan trigger key |
| Buzzer | Software programmable audio, 1KHz to 4KHz, |
| LED | Dual Color (Red/Green) LED Indicator |
| Application Software | |
| Operating System | Windows-base (2000/XP/Vista/Windows 7) |
| Data/Task Management | Job Generator Software |
| Scanner | |
| Scanner Type | Visible Laser Diode, 640~660 nm |
| Scan Speed | 80~120 scans/sec |
| Depth of Field | 5~65 cm |
| Connectivity | |
| Interface | Standard RS-232 & USB virtual RS-232 |
| Transmission Rate | 9600bps ~ 115200bps |
| Others | |
| Battery | Rechargeable Lithium Battery Pack (1700 mAh/ 3.7V) |
| Backup Battery | 3.0V, 18mAh,Maxell ML,Rech Lithium battery for SRAM |
| Operating Time | Over 24 hours/more than 28,000 scans (LCD Backlight Off) |
| Shock Resistance | 1.2m onto concrete |
| Compliance | FCC / CE / WEEE / RoHS |
| Weight | 175 g |
| Dimension(LxWxH:mm) | 145 x 64 x 31 |



Pegasus



Web: www.PegasusTech.net
E-Mail: Mkt@PegasusTech.net

Portable Data Collector